

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number  
**WO 2004/023719 A2**

(51) International Patent Classification<sup>7</sup>: **H04L 12/00**

20 Ezra Hasofer St., 46371 Herzliya (IL). **KIBEL, Danny**  
[IL/IL]; 24 Yavne'el St., 53603 Givatayim (IL).

(21) International Application Number:  
PCT/IL2003/000741

(74) Agent: **SWIRSKY, Daniel**; AlphaPatent Associates Ltd.,  
P.O.B. 2345, 99544 Beit Shemesh (IL).

(22) International Filing Date:  
8 September 2003 (08.09.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,  
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,  
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,  
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,  
RO, RU, SC, SE, SG, SK, SL, SY, TJ, TM, TN, TR,  
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/408,906 9 September 2002 (09.09.2002) US

(71) Applicant (*for all designated States except US*): **SHEER  
NETWORKS INC.** [US/US]; 555 N. Mathilda Ave., Suite  
9, SUNNYVALE, CA 94085 (US).


(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **NOY, Ariel** [IL/IL];

[Continued on next page]

(54) Title: **ROOT CAUSE CORRELATION IN CONNECTIONLESS NETWORKS**



(57) Abstract: A method for correlating routing errors to link failures in a network, the method including detecting a link failure between a first and a second router in a network, associating a first node address indicated in a first routing table of the first router with a first partition of the network, where a next hop of a packet destined for the first node address is the second router, associating a second node address indicated in a second routing table of the second router with a second partition of the network, where a next hop of a packet destined for the second node address is the first router, and correlating an error notification resulting from the failed delivery of a packet with the link failure where a source address of the packet corresponds to the first node address and a destination address of the packet corresponds to the second node address.

WO 2004/023719 A2

BEST AVAILABLE COPY



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *without international search report and to be republished upon receipt of that report*

## TITLE OF THE INVENTION

Root Cause Correlation in Connectionless Networks.

## FIELD OF THE INVENTION

5           The present invention relates to computer network technology in general, and in particular to correlation of network errors to root causes in connectionless networks.

## BACKGROUND OF THE INVENTION

10           Connectionless computer networks, such as Internet Protocol (IP) networks, are typically formed by connecting multiple routers to each other using either point-to-point connections or the Data Link Layer of the International Standard Organization's Open System Interconnect (ISO/OSI) network model, commonly referred to as "layer 2." One of the main features of a connectionless network is the ability of a network node, such as a PC, to connect directly to any of the routers and send/receive packetized data to/from any other  
15           network node connected to any other router. To accomplish this each node is typically uniquely identified by a unique network address, known in IP networks as an IP address.

          Routing of packets in a connectionless computer network is now described by way of example with reference to Fig. 1. When a node A sends a packet to a node B, A must specify the address of B as the destination address of the packet. The first router R1  
20           that accepts the packet forwards the packet to the next router R2 on the path to B, whereupon R2 forwards the packet to the next router R3 on the path to B, and so on. When the packet reaches the router to which B is directly connected, it is forwarded to B. It may thus be seen that, for any given destination address to which a packet is addressed, every router in the network should know the packet's next "hop," i.e., to which next router  
25           the packet is to be forwarded. Each router typically maintains this information in a routing table which contains a mapping between addresses or address groups, such as IP subnets, and the next hop for packets destined for these addresses.

30           When a link connecting two routers in a network fails, a partitioning of the network may occur. Thus in Fig. 1, if the link between R1 and R2 fails, nodes A and C can

still communicate with each other but not with nodes B and D, and vice versa. Each router will typically automatically detect this situation and update its routing table accordingly, such as by eliminating entries whose next hop is unreachable. However, nodes in one partition may still try to send packets to nodes in the other partition. When this occurs, a  
5 "no route to destination" error is typically generated and logged by the first router to detect the problem, which then reports the problem to the network management system (NMS). The NMS must then decide what action to take, such as tracing the error to its root cause. In large networks where there may be many active communication sessions between nodes at one time, a single link failure event might cause numerous "no route to destination"  
10 notifications to be generated in every router in one partition which receives packets that are destined for the other partition and reported to the NMS. Thus, where the existence of a link failure is already known to the NMS, it would be advantageous to know whether or not a routing error is caused by the link failure, as well as which nodes might be affected by the link failure, obviating the need for the NMS to take action that it would normally take.

15

### SUMMARY OF THE INVENTION

The present invention provides for the correlation of routing errors to link failures in a connectionless network.

In one aspect of the present invention a method is provided for correlating  
20 routing errors to link failures in a network, the method including detecting a link failure between a first and a second router in a network, associating a first node address indicated in a first routing table of the first router with a first partition of the network, where a next hop of a packet destined for the first node address is the second router, associating a second node address indicated in a second routing table of the second router with a second  
25 partition of the network, where a next hop of a packet destined for the second node address is the first router, and correlating an error notification resulting from the failed delivery of a packet with the link failure where a source address of the packet corresponds to the first node address and a destination address of the packet corresponds to the second node address.

30 In another aspect of the present invention any of the steps are performed with respect to a connectionless network.

In another aspect of the present invention a method the correlating step includes correlating a "no route to destination" error.

In another aspect of the present invention the associating steps comprise constructing a connectivity table.

5 In another aspect of the present invention the method further includes suppressing the error.

In another aspect of the present invention any of the steps are performed in a distributed network management system by at least one software agent associated with either of the routers.

10 In another aspect of the present invention the method further includes notifying at least one other agent in the network of the associations of the nodes to the partitions, where the other agent is not associated with either of the routers.

In another aspect of the present invention a method is provided for correlating routing errors to link failures in a network, the method including identifying a path between  
15 a first node and a second node in a network, detecting a link failure in the network, determining if the link failure lay along the path, and correlating an error notification resulting from the failed delivery of a packet with the link failure where a source address of the packet corresponds to an address of the first node, where a destination address of the packet corresponds to an address of the second node, and where the link failure lay along  
20 the path.

In another aspect of the present invention the identifying step includes identifying either of a most commonly used route and a most heavily used route between the nodes in accordance with a predefined measure of use.

25 In another aspect of the present invention any of the steps are performed with respect to a connectionless network.

In another aspect of the present invention the correlating step includes correlating a "no route to destination" error.

In another aspect of the present invention the method further includes suppressing the error.

In another aspect of the present invention any of the steps are performed in a distributed network management system by a software agent associated with either of the routers.

5 In another aspect of the present invention a system is provided for correlating routing errors to link failures in a network, the system including means for detecting a link failure between a first and a second router in a network, means for associating a first node address indicated in a first routing table of the first router with a first partition of the network, where a next hop of a packet destined for the first node address is the second router, means for associating a second node address indicated in a second routing table of  
10 the second router with a second partition of the network, where a next hop of a packet destined for the second node address is the first router, and means for correlating an error notification resulting from the failed delivery of a packet with the link failure where a source address of the packet corresponds to the first node address and a destination address of the packet corresponds to the second node address.

15 In another aspect of the present invention any of the means are operative with respect to a connectionless network.

In another aspect of the present invention the means for correlating is operative to correlate a "no route to destination" error.

20 In another aspect of the present invention the means for associating are operative to construct a connectivity table.

In another aspect of the present invention the system further includes means for suppressing the error.

25 In another aspect of the present invention a system any of the means are operative in a distributed network management system including at least one software agent associated with either of the routers.

In another aspect of the present invention the system further includes means for notifying at least one other agent in the network of the associations of the nodes to the partitions, where the other agent is not associated with either of the routers.

30 In another aspect of the present invention a system is provided for correlating routing errors to link failures in a network, the system including means for identifying a path between a first node and a second node in a network, means for detecting a link failure in

the network, means for determining if the link failure lay along the path, and means for correlating an error notification resulting from the failed delivery of a packet with the link failure where a source address of the packet corresponds to an address of the first node, where a destination address of the packet corresponds to an address of the second node, and where the link failure lay along the path.

In another aspect of the present invention the means for identifying is operative to identify either of a most commonly used route and a most heavily used route between the nodes in accordance with a predefined measure of use.

In another aspect of the present invention any of the means are operative with respect to a connectionless network.

In another aspect of the present invention the means for correlating step is operative to correlate a "no route to destination" error.

In another aspect of the present invention the system further includes means for suppressing the error.

In another aspect of the present invention any of the means are operative in a distributed network management system including a software agent associated with either of the routers.

## BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood and appreciated more fully from the following detailed description taken in conjunction with the appended drawings in which:

Fig. 1 is a simplified pictorial illustration of a network framework, useful in understanding present invention;

Fig. 2 is a simplified pictorial illustration of a network framework supporting error correlation, constructed and operative in accordance with a preferred embodiment of the present invention;

Fig. 3 is a simplified flowchart illustration of a method of correlation of routing errors to link failures in a connectionless network, operative in accordance with a preferred embodiment of the present invention.

Fig. 4 is a simplified flowchart illustration of a method of correlation of routing errors to link failures in a connectionless network supported by a distributed network

management system, operative in accordance with a preferred embodiment of the present invention; and

Fig. 5 is a simplified flowchart illustration of a method of identifying nodes that may be affected by link failures in a connectionless network, operative in accordance with a preferred embodiment of the present invention.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Reference is now made to Fig. 2, which is a simplified pictorial illustration of a network framework supporting error correlation, constructed and operative in accordance with a preferred embodiment of the present invention, and additionally to Fig. 3, which is a simplified flowchart illustration of a method of correlation of routing errors to link failures in a connectionless network, operative in accordance with a preferred embodiment of the present invention. In Fig. 2 a link 200 between two routers R1 and R2 is shown as having failed, as designated by an 'x' through link 200. Prior to the failure of link 200, a routing table 202 of router R1 shows that the next hop for packets destined for B and D is R2, while a routing table 204 of router R2 shows that the next hop for packets destined for A and C is R1. It may be seen that two partitions 206 and 208 (shown in dashed lines) are thus created in that nodes A and C cannot communicate with nodes B and D via link 200, and vice versa.

A network management system (NMS) 210 preferably maintains copies of routing tables 202 and 204. Having detected a link failure between R1 and R2, NMS 210 may create a connectivity table 212 indicating which nodes are in each of partitions 206 and 208. Since NMS 210 knows that R2 is inaccessible to R1 via link 200, NMS 210 may associate with partition 206 those node addresses in its copy of routing table 202 whose next hop is R2. Likewise, NMS 210 may associate with partition 208 those node addresses in routing table 204 whose next hop is R1. Should NMS 210 receive a "no route to destination" error notification from a network router together with the source and destination addresses of the packet that could not be delivered, NMS 210 may look up the source and destination addresses in connectivity table 212 to determine whether they are from different partitions. If both the source and destination addresses are from different partitions, then the "no route to destination" error notification may be an attempt to send



the packet across failed link 200. Thus, the error notification may be correlated with the link failure that is already known to NMS 210, and the error may be suppressed and need not be investigated further. Alternatively, the error notification should not be correlated with the link failure and may be investigated or otherwise acted upon by NMS 210.

5           Reference is now made to Fig. 4, which is a simplified flowchart illustration of a method of correlation of routing errors to link failures in a connectionless network supported by a distributed network management system, operative in accordance with a preferred embodiment of the present invention. In Fig. 4 the present invention is implemented in a distributed network management system, such as is described in U.S.  
10   Patent Application No. 09/799,637 and published as Published Application No. 20010039577, where every router has an associated software agent which continuously monitors the state of the router and its links. The agents monitoring R1 and R2 would thus detect the failure of link 200 and then communicate with each other to create connectivity table 212 which may then be provided to the agents of all other routers in the network.  
15   Thus, when any router Rx encounters a "no route to destination" error, its associated agent looks up the source and destination addresses in connectivity table 212 to determine whether they are from different partitions, and action may be taken or the error notification ignored as described above.

          Reference is now made to Fig. 5, which is a simplified flowchart illustration of a  
20   method of identifying nodes that may be affected by link failures in a connectionless network, operative in accordance with a preferred embodiment of the present invention. In Fig. 5 a list of virtual paths in a network is maintained, where each virtual path represents the traversal of the links, routers, and other network elements comprising the most commonly used and/or most heavily used routes between network nodes, as determined  
25   using any predefined measure of use. The virtual path list may be maintained centrally, such as by NMS 210, or in a distributed manner, such as by one or more agents in a distributed network management system. The virtual path list may be created using any conventional technique, such as by identifying common access patterns in router access lists, analyzing network failure alarms (e.g., packet lost, no route, etc.) to determine traffic flow, and  
30   determining network tomography from traffic counter patterns. When a failed link is detected, each virtual path may be checked using any known technique to determine if it is

broken and, if so, which nodes and other network elements along the path are affected. Thereafter, should a "no route to destination" error be encountered where the source address of the packet being sent belongs to the node at one end of a virtual path known to have a failed link, and the packet's destination address belongs to the node at the other end of the virtual path, the error may be correlated to the failed link and action may be taken or suppressed as described hereinabove.

It is appreciated that one or more of the steps of any of the methods described herein may be omitted or carried out in a different order than that shown, without departing from the true spirit and scope of the invention.

While the methods and apparatus disclosed herein may or may not have been described with reference to specific hardware or software, it is appreciated that the methods and apparatus described herein may be readily implemented in hardware or software using conventional techniques.

While the present invention has been described with reference to one or more specific embodiments, the description is intended to be illustrative of the invention as a whole and is not to be construed as limiting the invention to the embodiments shown. It is appreciated that various modifications may occur to those skilled in the art that, while not specifically shown herein, are nevertheless within the true spirit and scope of the invention.

## CLAIMS

What is claimed is:

1. A method for correlating routing errors to link failures in a network, the method comprising:

5 detecting a link failure between a first and a second router in a network;  
associating a first node address indicated in a first routing table of said first router with a first partition of said network, wherein a next hop of a packet destined for said first node address is said second router;

10 associating a second node address indicated in a second routing table of said second router with a second partition of said network, wherein a next hop of a packet destined for said second node address is said first router; and

correlating an error notification resulting from the failed delivery of a packet with said link failure where a source address of said packet corresponds to said first node address and a destination address of said packet corresponds to said second node address.

15

2. A method according to claim 1 wherein any of said steps are performed with respect to a connectionless network.

3. A method according to claim 1 wherein said correlating step comprises  
20 correlating a "no route to destination" error.

4. A method according to claim 1 wherein said associating steps comprise constructing a connectivity table.

25 5. A method according to claim 1 and further comprising suppressing said error.

6. A method according to claim 1 wherein any of said steps are performed in a distributed network management system by at least one software agent associated with either of said routers.

30

7. A method according to claim 6 and further comprising notifying at least one other agent in said network of said associations of said nodes to said partitions, wherein said other agent is not associated with either of said routers.

5 8. A method for correlating routing errors to link failures in a network, the method comprising:

identifying a path between a first node and a second node in a network;

detecting a link failure in said network;

determining if said link failure lay along said path; and

10 correlating an error notification resulting from the failed delivery of a packet with said link failure where a source address of said packet corresponds to an address of said first node, where a destination address of said packet corresponds to an address of said second node, and where said link failure lay along said path.

15 9. A method according to claim 8 wherein said identifying step comprises identifying either of a most commonly used route and a most heavily used route between said nodes in accordance with a predefined measure of use.

10. A method according to claim 8 wherein any of said steps are performed with  
20 respect to a connectionless network.

11. A method according to claim 8 wherein said correlating step comprises correlating a "no route to destination" error.

25 12. A method according to claim 8 and further comprising suppressing said error.

13. A method according to claim 8 wherein any of said steps are performed in a distributed network management system by a software agent associated with either of said routers.

14. A system for correlating routing errors to link failures in a network, the system comprising:

means for detecting a link failure between a first and a second router in a network;

5 means for associating a first node address indicated in a first routing table of said first router with a first partition of said network, wherein a next hop of a packet destined for said first node address is said second router;

means for associating a second node address indicated in a second routing table of said second router with a second partition of said network, wherein a next hop of a packet destined for said second node address is said first router; and

10 means for correlating an error notification resulting from the failed delivery of a packet with said link failure where a source address of said packet corresponds to said first node address and a destination address of said packet corresponds to said second node address.

15 15. A system according to claim 14 wherein any of said means are operative with respect to a connectionless network.

16. A system according to claim 14 wherein said means for correlating is operative  
20 to correlate a "no route to destination" error.

17. A system according to claim 14 wherein said means for associating are operative to construct a connectivity table.

25 18. A system according to claim 14 and further comprising means for suppressing said error.

19. A system according to claim 14 wherein any of said means are operative in a distributed network management system comprising at least one software agent associated  
30 with either of said routers.

20. A system according to claim 19 and further comprising means for notifying at least one other agent in said network of said associations of said nodes to said partitions, wherein said other agent is not associated with either of said routers.

5 21. A system for correlating routing errors to link failures in a network, the system comprising:

means for identifying a path between a first node and a second node in a network;

means for detecting a link failure in said network;

10 means for determining if said link failure lay along said path; and

means for correlating an error notification resulting from the failed delivery of a packet with said link failure where a source address of said packet corresponds to an address of said first node, where a destination address of said packet corresponds to an address of said second node, and where said link failure lay along said path.

15

22. A system according to claim 21 wherein said means for identifying is operative to identify either of a most commonly used route and a most heavily used route between said nodes in accordance with a predefined measure of use.

20 23. A system according to claim 21 wherein any of said means are operative with respect to a connectionless network.

24. A system according to claim 21 wherein said means for correlating step is operative to correlate a "no route to destination" error.

25

25. A system according to claim 21 and further comprising means for suppressing said error.

26. A system according to claim 21 wherein any of said means are operative in a distributed network management system comprising a software agent associated with either  
30 of said routers.

1/5




Fig. 1

2/5




Fig. 2






Fig. 3




Fig. 4

5/5




Fig. 5

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number  
**WO 2004/023719 A3**

(51) International Patent Classification<sup>7</sup>: **H04L 12/24**

20 Ezra Hasofer St., 46371 Herzliya (IL). **KIBEL, Danny**  
[IL/IL]; 24 Yavne'el St., 53603 Givatayim (IL).

(21) International Application Number:  
PCT/IL2003/000741

(74) Agent: **SWIRSKY, Daniel**; AlphaPatent Associates Ltd.,  
P.O.B. 2345, 99544 Beit Shemesh (IL).

(22) International Filing Date:  
8 September 2003 (08.09.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/408,906 9 September 2002 (09.09.2002) US

(71) Applicant (*for all designated States except US*): **SHEER NETWORKS INC.** [US/US]; 555 N. Mathilda Ave., Suite 9, SUNNYVALE, CA 94085 (US).


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **NOY, Ariel** [IL/IL];

[Continued on next page]

(54) Title: **ROOT CAUSE CORRELATION IN CONNECTIONLESS NETWORKS**



(57) Abstract: A method for correlating routing errors to link failures in a network, the method including detecting a link failure between a first and a second router in a network, associating a first node address indicated in a first routing table of the first router with a first partition of the network, where a next hop of a packet destined for the first node address is the second router, associating a second node address indicated in a second routing table of the second router with a second partition of the network, where a next hop of a packet destined for the second node address is the first router, and correlating an error notification resulting from the failed delivery of a packet with the link failure where a source address of the packet corresponds to the first node address and a destination address of the packet corresponds to the second node address.

WO 2004/023719 A3

BEST AVAILABLE COPY



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

**(88) Date of publication of the international search report:**

6 May 2004

# INTERNATIONAL SEARCH REPORT

International application No  
PCT/IL 03/00741

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L12/24

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC, COMPENDEX, IBM-TDB

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>WO 01/19038 A (ERICSSON TELEFON AB L M) 15 March 2001 (2001-03-15)</p> <p>Provides system that discover link failure and recover quickly by rerouting communications along alternate route, even if communication link between two nodes in real time system fails. Using timer. page 2, line 28 - line 31 page 7, line 21 - page 8, line 4 page 9, line 19 - line 28 page 15, line 13 - page 16, line 5 page 17, line 1 - line 18 page 8, line 5 - line 16 page 22, line 4 - line 6 page 13, line 10 - page 14, line 5</p> <p style="text-align: center;">-/--</p>	<p>1-5, 8-12, 14-18, 21-25</p>

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \* & \* document member of the same patent family

Date of the actual completion of the international search

10 March 2004

Date of mailing of the international search report

23/03/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Ngao, Y.S.

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/IL 03/00741

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>US 6 377 677 B1 (KEY PETER B ET AL) 23 April 2002 (2002-04-23)</p> <p>routing calls in a network in which a destination has a single network number and two network addresses. successive calls are directed to available one of the network address in a sequential manner. column 2, line 11 - line 29 column 2, line 49 - line 61 column 4, line 25 - line 34 column 5, line 64 - column 6, line 9 column 8, line 11 - line 45</p>	<p>1,2,8, 10,14, 15,21,23</p>
A	<p>US 2002/103631 A1 (FELDMANN ANJA ET AL) 1 August 2002 (2002-08-01)</p> <p>constructing a data model of a network comprising data object and routing model network nodes and links, based on traffic demand and topology information received as input. paragraph '0014! paragraph '0029! - paragraph '0030! paragraph '0051! paragraph '0060!</p>	<p>1-5, 8-12, 14-18, 21-25</p>
A	<p>C BOUTREMANS, G IANNACCONE, C DIOT: "Impact of link failures on VoIP performance" SPRINT ADVANCED TECHNOLOGY LABS, 'Online! 12 May 2002 (2002-05-12), pages 1-9, XP002273053 Retrieved from the Internet: URL:<a href="http://www.sprintlabs.com/People/gianluca/papers/voip.pdf">http://www.sprintlabs.com/People/gianluca/papers/voip.pdf</a> 'retrieved on 2004-03-08! link failures may be followed by long periods of routing instability, during which packets can be dropped because forwarded along invalid paths. page 1, left-hand column, line 8 - line 10 page 1, right-hand column, line 26 - line 30 page 5, right-hand column, line 15 - line 21 page 5, right-hand column, line 55 - line 61 page 7, left-hand column, line 7 - line 25 page 8, left-hand column, line 56 - line 62</p>	<p>1-5, 8-12, 14-18, 21-25</p>

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IL 03/00741

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0119038	A	15-03-2001	WO 0119038 A1	15-03-2001
			AU 1420500 A	10-04-2001
			DE 19983979 T0	01-08-2002
			GB 2371944 A ,B	07-08-2002
US 6377677	B1	23-04-2002	AU 5402698 A	17-07-1998
			EP 0948868 A1	13-10-1999
			WO 9828924 A1	02-07-1998
			JP 2001507187 T	29-05-2001
US 2002103631	A1	01-08-2002	US 2002101821 A1	01-08-2002



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**